Carbon Dioxide





Effective Class B and C fire protection

These quality wheeled fire extinguisher models are designed for single person use and operation. They are extremely versatile and ready to tackle flammable liquid and electrical equipment fire hazards. They are ideally suited for industrial applications where delicate equipment or processes require a clean extinguishing agent.

Carbon Dioxide is an effective and clean gaseous extinguishing agent that leaves no residue to clean up. These models are suitable for use on Class B and C fires.

Features:

- Heavy-duty hand wheel cylinder activation valves
- 16 inch semi-pneumatic rubber wheels
- Quick release discharge nozzle retainer
- Heavy-duty industrial discharge valve and nozzle
- UL Listed—Meets D.O.T. requirements
- Five year periodic hydrostatic test interval
- Six year warranty
- CD-50 model equipped with 15' hose length
- CD-100 model equipped with 40' hose length





Technical Data:

BADGER Wheeled Carbon Dioxide Self-Expelling Models

CD50-1	CD100-1
22724	22725
50	100
22.68	45.36
20-B:C	20-B:C
Carbon Dioxide	Carbon Dioxide
Steel	Steel
Brass	Brass
n/a	n/a
Carbon Dioxide	Carbon Dioxide
850	850
-40 to 120	-40 to 120
-40.0 to 48.9	-40.0 to 48.9
n/a	n/a
n/a	n/a
30	60
10.0	10.0 to 15.0
3.85	3.65 to 4.57
52	52
132.1	132.1
21.5	32
54.61	81.28
33	33
83.8	83.8
271	446
122.9	202.3
n/a	n/a
	22724 50 22.68 20-B:C Carbon Dioxide Steel Brass n/a Carbon Dioxide 850 -40 to 120 -40.0 to 48.9 n/a n/a 30 10.0 3.85 52 132.1 21.5 54.61 33 83.8 271

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

Distributed by:







